

Tiandy



TC-H354S Spec:23X/I/E/V3.1

5MP 23× Starlight IR POE AI PTZ Camera—Qatar

Pro Series



KEY FEATURES

- Up to 2880×1620@30fps
- Optical zoom: 23×, digital zoom 16×
- Smart IR, IR Range: 150m
- S+265/H.265/H.264/M-JPEG
- Intelligent monitoring
- Support Human/Vehicle Classification
- Plug-in Free
- IP66, IK10 (Optional)



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596065
Fax: +86-22-58596048

Tiandy




SPECIFICATIONS

Camera	
Image Sensor	1/2.7" CMOS
Min. Illumination	Color: 0.001lux@ (F1.6, AGC ON), B/W: 0lux with IR
Shutter Time	1s to 1/100,000s
Day&Night	IR Cut Filter with Auto Switch
WDR	120dB
S/N	> 39dB
Lens	
Focal Length	5mm~115mm
Optical Zoom	23X
Digital Zoom	16X
Zoom Speed	<5S
Aperture Range	F1.67~3.67
Field of View	Horizontal filed of view: 58° (w)~3.0° (t) Vertical filed of view: 39.7° (w)~2.2° (t) Diagonal field of view:63.1°(w)~3.7°(t)
Focus Control	Auto,semi-auto>manual
Iris Control	Auto
Close Focus Distance	500mm~5000mm
DORI Distance	Detect:1980m Observe:785m Recognize:396m Identify:198m
Pan&Tilt	
Pan Range	360°
Pan Speed	Pan Manual Speed: 0.1°~80°/s, Pan Preset Speed: 80°/s
Tilt Range	-16°~90° (Default -3°~90°)
Tilt Speed	Tilt Manual Speed: 0.1°~80°/s, Tilt Preset Speed: 80°/s
3D Position	Yes
Preset	500
Cruise	16, up to 32 presets per cruise
Scan	8
Pattern	8, each with 600s memory or 1000 orders
Scheduled Task	Preset,Cruise,Scan,Pattern
North Point	Yes(Manual setting)
Power-off Memory	Yes
Preset Freezing	N/A
Illuminator	
IR LEDs	7
IR Distance	Up to 150m
Wavelength	850nm
IR Irradiation Angle	Adjustable by Zoom
White LEDs	N/A
Whitelight Distance	N/A
Laser	N/A
Laser Distance	N/A
Compression Standard	
Video Compression	S+265/H.265/H.264/M-JPEG
Video Bit Rate	32Kbps~16Mbps
Audio Compression	G.711A/G.711U/ADPCM_D/AAC_LC
Audio Sampling Rate	8kHz/32kHz/48kHz
Image	
Max. Resolution	2880×1620@30fps
Main Stream	PAL:25fps (2880×1620,2688x1520,2560×1440,2304×1296,1920×1080,1280×720) NTSC:30fps (2880×1620,2688x1520,2560×1440,2304×1296,1920×1080,1280×720)
Sub Stream	PAL:25fps(704x576,704x288,352x288,640x360) NTSC:30fps(704x480,704x240,352x240,640x360)
Third Stream	PAL:25fps(704×576,704×288,352×288,640×480) NTSC:30fps(704×480,704×240,352×240,640×480)
BLC	Yes
HLC	Yes
AGC	Yes



Noise Reduction	2D/3D
White Balance	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/Incandescent lamp/ Locked white balance
ROI	7 Dynamic Areas for Both Main and Sub Stream
EIS	N/A
OSD	16x16, 24x24,32x32, 48x48, 64x64,96x96, adaptable size, Letters such as Week, Date, Time, Total 5 Regions
Defog	Digital
Flip	Yes
Regional Exposure	Yes
Regional Focus	Yes
Demist	Yes
Feature	
Alarm Trigger	Motion Detection;Mask Alarm;Voltage Alarm;Disk Full;Disk R/W Error;IP Address Conflict; MAC Address Conflict;FTP Server Exception ;Event Input, Event Output
Linkage Method	send email;trigger sound;trigger recording;trigger capture;notify surveillance center
Video Analytics	Human/Vehicle Classification;Tripwire;Double Tripwire;Perimeter;Object Abandon;Object Lost;Heatmap; Loitering;Running;Parking;People Counting;Crowded;Safety Helmet Detection;On Duty Detection; Video Abnormal;Audio Abnormal
Early Warning(EW)	N/A
Auto-Tracking	N/A
Face Mode	Face Capture
Face Caputure Performance	Detects up to 32 faces at the same scene
Network	
ANR	Auto store video in SD card when NVR disconnected, and upload video to NVR when resumed connection (Only Support Tiandy ANR NVR)
Protocols	HTTP;HTTPS;TCP/IP;UDP;UPnP;SNMP;DHCP;DNS;DDNS;Easy DDNS;NTP;SMTP;SSL;802.1X;QoS;IPv4;IPv6; PPPOE;SSH;Unicast;Multicast;RTP;SRTP;RTSP;FTP;SFTP;NAS
System Compatibility	ONVIF Profile S/T/G/M;CGI;Milestone;RTMP
Remote Connection	≤7
User/Host	Up to 32 users. 4 user levels
Client	Easy7 Smart Client
Moblle Client	EasyLive Plus
Web	IE 10+;Firefox52+;Edge89+;Safari11+;Chrome57+
Interface	
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port
Audio I/O	1/1
Alarm I/O	1/1
Built-In Speaker	N/A
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512 GB
RS-485	N/A
BNC	N/A
Wiper	N/A
Electronic Compass	N/A
GPS/BDS	N/A
General	
Web Client Language	19 languages Simple Chinese/English/Traditional Chinese/Spanish/Italian/ Korean/Turkish/Russian/Thai/ Polish/French/Dutch/ Hebraism/Vietnamese/Arabic/German/ Ukrainian /Portuguese/Albanian
Operating Temperature	-30°C~65°C(IR OFF) -30°C~40°C(IR ON)
Operating Humidity	0-95%
Storage Temperature	-30°C~65°C
Storage Humidity	0-95%(non-condensing)
Power Supply	DC12V±10%/POE+(IEEE802.3 at)
Power Consumption	8.1W (IR OFF), 19.4W (IR ON)
Protection	IP66 , IK10 (Optional)
Heater	N/A
Material	ADC 12, PC+ABS
Boundary Dimensions	161(D)276(H)mm
Package Dimensions	260(L)260(W)465(H)mm
GrossWeight	3.9kg
NetWeight	2.2kg

DIMENSIONS



Unit: mm

INCLUDED




TC-P52BM Spec: 4
Wall Mount

ACCESSORIES



DF21Y
Pendant Mount



A35
Corner Mount



811
Junction Box

DISTRIBUTED BY



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596178
Fax: +86-22-58596048