



TC-C32RN Spec:I5/E/QX/4mm/VJ04.2

Dual 2MP Fixed IR Bullet Camera

Spark Series



KEY FEATURES

B'Sef[UZage[Y
Gb fa ? Sj ž#+\$" ° # " * " d'ea'gf[a`
EŁ\$(' !: Ž\$(' !: Ž\$(&4!: Ž\$(&? !: Ž\$(&
5a'ad" Ž' \$>gj 2/8#ž{395 A@fi4!l , ">gj i [fZ ;D
E_ Sdf ;Dl;D dS` YW " _

Egbbadfe_ Sdf egdhV^S` UW
AbWsf[YUa` V[f[a` eŽ% p(" l: g_ [V[fk +' , adWe/ a
Ua` VW eSf[a` fi
65#\$Hf \$' , ł? Sj ž) ž l IBA 7 * " \$ŽSX? Sj ž*ž l
;B()



Tiandy Technologies Co.,Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com

Website: en.tiandy.com

Tel: +86-22-58596065


Fax: +86-22-58596048

SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
WDR	DWDR
S/N	>36dB
Angle Adjustment	0~350°(P); 0~90°(T); 0~360°(R)
Lens	
Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.6
Field of View	78.3°(H); 44.1°(V); 89.3°(D)
DORI Distance	Detect:60.38m Observe:23.96m Recognize:12.08m Identify:6.04m
Illuminator	
IR LEDs	6
IR Distance	50m
Wavelength	850nm
Compression Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz
Image	
Main Stream	PAL:25fps(1920×1080, 1280×720, 640×480, 704×576) NTSC:30fps(1920×1080, 1280×720, 640×480, 704×480)
Sub Stream	PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48
Privacy Mask	4 black static areas
Defog	Yes

Feature	
Alarm Trigger	Motion Detection; IP Address Conflict
Linkage Method	trigger capture
Network	
Protocols	HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; IPv4; SSH; Unicast; RTSP; FTP
System Compatibility	P2P(Mutually exclusive with Profile G); ONVIF Profile S/T; CGI; Milestone
Remote Connection	≤2
Client	Easy7 Smart Client
Moblle Client	EasyLive Plus
Interface	
Communication Interface	1*RJ-45,10/100 Mbps self-adaptive Ethernet port
General	
Web Client Language	18 languages
	Simple Chinese/Traditional Chinese/English/Spanish/Korean/Italian/Turkish/Russian/Thai/ French/Polish/Dutch/Hebrew/Arabic/Vietnamese/German/Ukrainian/Portuguese
Operating Temperature	-30℃~60℃
Operating Humidity	Humidity 95% or less (no condensation)
Storage Temperature	-30℃~60℃
Storage Humidity	Humidity 95% or less (no condensation)
Power Supply	DC12V±25%,MAX 7.5W; POE 802.3af,MAX 8.5W
Protection	Surge4000V; ESD6000V; IP67
Boundary Dimensions	260(L)133(W)140(H)mm
Package Dimensions	315(L)145(W)140(H)mm
GrossWeight	0.87kg

DIMENSIONS (Unit: mm)





Assembly diagram of Junction Box