


Tiandy

TC-P3601 Spec:O/10

10.1-inch Door Station



KEY FEATURES

- 10.1-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Open the door by face recognition (10,000 users)
- Liveness detection
- Open the door by IC card (100,000 users)
- 2MP camera with WDR mode

SPECIFICATIONS

Physical	
System	Android
Front Panel	Aluminum
Power Supply	PoE (802.3af) or DC 12V/2A
Standby Power	3 W
Rated Power	13 W
Camera	2MP, CMOS, WDR
IR Sensor	Support
Wiegand Port	Support
Ethernet Port	1 x RJ45, 10/100 Mbps adaptive
Door Entry	Face, IC card (13.56MHz), PIN code
RS485 Port	1
Relay Out	1
Exit Button	1
Door Magnetic	1
IP Rating	IP65 (Seal up the cracks between door station and the wall with glass glue.)
Installation	Flush Mounting
Dimension	400 x 180 x 45 mm
Working Temperature	-20°C to +55°C
Storage Temperature	-40°C to +70°C
Working Humidity	10% to 90% (non-condensing)
Display	
Display	10.1-inch TFT LCD
Screen	10.1-inch capacitive touch screen
Resolution	1024 x 600
Audio	
Audio Codec	G.711
Echo Cancellation	Yes
DTMF	RFC2833
Microphone	Built-in microphone
Speaker	Built-in speaker
Video	
Video Codec	H.264
Video Resolution	Up to 1920 x 1080
Viewing angle	100°(D)
Max. Image Transfer Rate	1080p – 25fps
Light Compensation	LED white light
Networking	
Protocol	SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP
Package Features	

Qty/CTN	6 pcs
N.W/PCS	3.04 kg
G.W/CTN	22.18 kg
Giftbox Size	465 x 255 x 140mm
Carton Size	860 x 485 x 280 mm



Tiandy Technologies Co.,Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com

Tel: +86-22-58596065

Website: en.tiandy.com

Fax: +86-22-58596048