



TC-P3701 Spec:J

License Plate Recognition Integrate Machine



KEY FEATURES

- License plate recognition accuracy is over 99.7%
- License plate recognition speed is less than 200 ms
- No need to stop and swipe card
- Quick access to the parking lot
- More intelligent, more convenient, perfect user experience
- Real-time display of license plate number, time record, remaining empty parking spaces, parking fee and other information
- Localized voice broadcast
- Camera, LED display, voice broadcast, fill light, fixed base as integrated design

SPECIFICATIONS

LPR specification	
Recognition Rate	Day \geq 99.9%; Night \geq 99.7%
Recognition Distance	2-10Meters (Recommend Best Distance is 3.5-4m)
Recognition Time	\leq 200ms (Average)
Communication	TCP/IP
Interface	2 Relay, 2 Aux. Input, Audio Input And Output, 2 485 Output, Reset, Wiegand Out
Camera Lens	2MP, Auto Focus, Best Snap Range: 3.5-4Meters
Minimum Illumination	0.1Lux (Standard)
Standard Function	Automatic License Plate Recognition, Real-Time Display Information, Voice Broadcast ,Customizable Charging Rules, Export Various Financial Statements, Blacklist And Whitelist Function, Fill Light ,Automatic Control Parking Barrier
Support Speed	15km/h
Support Country	Argentina, Mexico, Chile, Peru, Colombia , Thailand Malaysia, Indonesia, Vietnam, UAE, Saudi Arabia, Turkey, Oman, South Africa, Egypt, Brazil, EU, Mongolia, Korea, Pakistan
Physical Specifications	
Power Consumption	80W
Power Supply	220V AC 50Hz
Operating Temperature	-20°C - +55°C
Relative Humidity	10%-90%
Weight	30Kg
Package Dimension(LxWxH)	340x220x1600 mm



Tiandy Technologies Co.,Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com

Website: en.tiandy.com

Tel: +86-22-58596065

Fax: +86-22-58596048