



TC-P3701 Spec:l

## Mini LPR



### KEY FEATURES

- Using the LPR system, there is no need to stop the vehicle or swipe any card.
- Vehicles could quickly access the parking lot when they have passed the automatic license plate recognition, providing users with more intelligent, convenient, and perfect experiences.
- The multi-functional product is integrated with a license plate recognition camera, LED display, fll light, column and bracket.
- It looks simple and elegant. Also, it is widely used in parking lot management.

### SPECIFICATIONS

License Plate Recognition Specifications	
License Plate Number	100W (Max. 120W)
Recognition Accuracy	
Recognition Speed	≤100ms
Classification	License plate number
Adaptable Speed of Car	Up to 40km/h
Recognition Distance	3m to 10m (the recommended distance is 3m to 5m)

<b>Output Information</b>	License plate number, License plate picture, Access time
<b>Supported Regions</b>	Thailand, Argentina, Mexico, Chile, Colombia, Saudi Arabia, Brazil, Peru, Mongolia, Mainland China, Indonesia, Uzbekistan, India, Myanmar, Vietnam, Cambodia, etc.
<b>Offline Working Parameters</b>	
<b>Allowlist</b>	1,000
<b>Blocklist</b>	1,000
<b>Monthly Parking</b>	8,000
<b>Entry and Exit Records</b>	10,000
<b>Captured Pictures</b>	10,000
<b>Camera Parameters</b>	
<b>Image Sensor</b>	1/2.8" 3MP CMOS sensor
<b>Illumination</b>	0.1Lux (Default)
<b>Lens</b>	Autofocus (from 3.2mm to 11.1mm)
<b>Resolutions</b>	2304*1296P, 1920*1080, 1280*720P, 704*576P
<b>Compression</b>	H.264 / H.265 / MJPEG
<b>Frame Rate</b>	1 to 25 frames; 25 frames by default (1920*1080 pixels)
<b>Communication Protocol</b>	TCP/IP (10/100Mbps), RTSP, P2P, PUSH
<b>I/O Interface</b>	Two relays, RS485, AUX I/O, Barrier status input, Wiegand in and out
<b>SD Storage</b>	Default 8GB, maximum support 128GB
<b>Picture Format</b>	JPG
<b>How to Start Recognition</b>	Video trigger (by default), loop detection
<b>Protection Level</b>	IP65
<b>Rated Power</b>	80W
<b>Voltage</b>	12V
<b>Working Temperature</b>	-20°C to 55°C
<b>Working Humidity</b>	≤90%
<b>Height</b>	1.2m to 1.8m (adjustable)
<b>Dimensions (mm)</b>	1140*500*310
<b>Product Components</b>	
<b>LPR Camera</b>	1
<b>Column</b>	1
<b>Fill light</b>	1
<b>LED Display (Optional)</b>	1

