

 Tiondy
 Itanuy
 Itanuy<

How to activate devices in bulk on searchconfigtool

Description: This document will show you how to activate devices in bulk on searchconfigtool

Note: This feature requires downloading the searchconfigtool tool

Part 1: Preparations

Preparation of the device

- 1.1 Connect the computer and device under the same local area network
- 1.2 Download the searchconfigtool tool. Tiandy Technologies

← C ▲ 不安全 en.tiandy.com/index.php?s=/h	Home/Article/lists/category/131.html		- H	A¢ as s'à	12≣	G 🙆	۲	··· (6
Su	pport								
Q	uick Start Guide Troubl	e Shooting Download Center Notes							
Image: Participation of the second	Home - Support - Download Cer	ter - Tool & VMS							
		Download Center							
E	Brochures Tool & VMS	SDK Firmware Product Installation Certificates							
		a, noo soora noos sa asimtisaas maninisin tiga oquito j							
٦		- Down	nicad						
	Name	SearchConfig Tool Install V2.0(build 23.0129)							
	Describe	SearchConfig Tool Install V2.0(build 23.0129)_SP1							
		Dowr	nload						
	Name	SearchConfig Tool Install Mac64 V2.0(build 23.0112)							
	Describe	SearchConfig Tool Install Mac64 V2.0(build 23.0112)							

Device icon



Section 2: How to Activate Devices in Bulk



1.1 Search for the device you want to activate on the tool.

SearchConfig	Too	I V2	2.0					2 Refresh	🖶 Tool 🗸 🔇 I	.anguage	- I @ I	łelp ▾ = □ ×
Device Operation 🔺	O Al		PC/PTZ C	NVR/XVR	Device Model All			 Kernel Version 	All	Hardware V	ersion All	•
Login		No.	Туре	Status	Address	Channels	Code		Device Model	E Versio	S/N	Kernel Version
Logout	0	1	IPC/PTZ	Logout	192.168.1.2(non	1		TC-C32QN SPEC:	:13/E/Y/4mm/V5.0	6.1.2		NVSS_V26.1.0.2021
Reboot Device		2	IPC/PTZ	Logout	192.168.1.2(non	1		TC-C32TS SPEC:I	8/A/E/Y/M/H/2.7-13.5mm/V4.1	6.1.2	485407C308	NVSS_V30.0.0.2022
Forgot Password												
Change Password												
Restore Default												
Upgrade Device												
Export List												
	_											
Device Setting 🔻	Devic	e: 2 C	ount: 0									

1.2 Action Configuration - > Device Activation and select the device you want to activate.

SearchConfig Tool V2.0								🔁 Refresh	🖻 Tool 🕶 🔇 I	anguage	- I ⊘ F	lelp 👻 — 🗆 🗙
Device Operation 🔻	O A	All O IPC/PTZ O NVR/XVR Device Model All K						 Kernel Version All Hardware Version All 				
Device Setting		No.	Туре	Status	Address	Channels	Code		Device Model	E Versio	S/N	Kernel Version
Network Parameters		1	IPC/PTZ	Logout	192.168.1.2(non	1		TC-C32QN SPEC:	13/E/Y/4mm/V5.0	6.1.2		NVSS_V26.1.0.2021
Network Customization		2	IPC/PTZ	Logout	192.168.1.2(non	1		TC-C32TS SPEC:18	B/A/E/Y/M/H/2.7-13.5mm/V4.1	6.1.2	485407C308	NVSS_V30.0.0.2022
Codec Settings	Ч											
OSD Settings												
NTP Settings												
Remote Service												
Access Platform												
Add Device												
Clear Added Device												
Search Setting												
Activate Device												
Disk Cleanup												
Advance Search Config												
WireLessRouteSet												
		-		_			-	_		_	_	
	Devie	ce: 2 Ce	ount: 2									

1.3 Enter the password you want to set



Tiandy Technologies Co., Ltd.

Tiandy Technologies Co., Ltd.

SearchConfig 1	Гоо	I V2	2.0					2 Refresh	💼 Tool 👻 丨	🚯 Lai	nguage	- I @ I	$lelp \bullet - \Box \times$
Device Operation 🔹	• All O IPC/PTZ O NVR/XVR Device Model All									▼ Ha	rdware V	/ersion All	•
Device Setting		No.	Туре	Status	Address	Channel	s Code	Dev	vice Model		E Versio	S/N	Kernel Version
Network Parameters		1	IPC/PTZ	Logout	192.168.1.2(non		1	TC-C32QN SPEC:13/E/	Y/4mm/V5.0		6.1.2		NVSS_V26.1.0.2021
Network Customization		2	IPC/PTZ	Logout	192.168.1.2(non		1	TC-C32TS SPEC:18/A/E	/Y/M/H/2.7-13.5mm	n/V4.1	6.1.2	485407C308	NVSS_V30.0.0.2022
Codec Settings													
OSD Settings													
NTP Settings					Activate Device			~					
Remote Service					Activate Device			^					
Access Platform	User Name admin												
Add Device					New Passy	word]				
Clear Added Device						Plea: or m	e enter a 8 ore combi	-15 digit password, two nations of numbers.					
Search Setting						lowe	rcase letter	s, and uppercase letters	5				
Activate Device					New Password confirma	ation							
Disk Cleanup								Activate]				
Advance Search Config													
WireLessRouteSet													
	_						-		-				
	Devic	e: 2 C	ount: 2										

1.4 Device activation successful

SearchConfig	Гоо	l V2	2.0						🔁 Refresh		🖆 Tool 👻 🕴 🔇 L	anguage	- I ⊘ F	łelp ▼
Device Operation 🔹 🔻	▼ O All ◯ IPC/PTZ ◯ NVR/XVR Device Model All ▼ Ke							Kernel Version	All		lardware V	ersion All	•	
Device Setting 🔺		No.	Туре	Status	А	ddress	Channels	Code		De	vice Model	E Versio	S/N	Kernel Version
Network Parameters		1	IPC/PTZ	Logout	192.16	3.1.2	1		TC-C32QN SPEC:	13/E/	/Y/4mm/V5.0	6.1.2		NVSS_V26.1.0.2021
Network Customization		2	IPC/PTZ	Logout	192.16	3.1.2	1		TC-C32TS SPEC:18	B/A/E	E/Y/M/H/2.7-13.5mm/V4.1	6.1.2	485407C308	NVSS_V30.0.0.2022
Codec Settings														
OSD Settings					log				×					
NTP Settings					1 IN	FO [3C:DA	A:6D:C9:AC:3B]:I	Device ad	tive successfully.					
Remote Service					2 IN	FO [3C:DA	A:6D:BF:C0:6A]:E	evice ac	tive successfully.	Ì				
Access Platform					3 IN	FO Comp	eled(2).Success	ful(2),Fai	ed(0),Not operat	•				
Add Device														
Clear Added Device										rc	D			
Search Setting										n	s			
Activate Device														
Disk Cleanup									Activ	/ate				
Advance Search Config														
WireLessRouteSet														
		2.0			-	_		-		-	_	-		
	Devic	e: 2 Ce	ount: 2											

1.5 When there is no red flag, it means that the device and activation are successful.



Tiandy Technologies Co., Ltd.

SearchConfig	Гоо	I V2	2.0					2 Refresh	💼 Tool 🗸 🔇	Language	- I @ I	Help $ \Box$ \times
Device Operation 🔻	O All		PC/PTZ C	NVR/XVR Device	Model All		•	Kernel Version	All 👻	Hardware	/ersion All	•
Device Setting		No.	Туре	Status	Address	Channels	Code		Device Model	E Versio	s S/N	Kernel Version
Network Parameters		1	IPC/PTZ	Logout	192.168.1.2	1		TC-C32QN SPEC:13	/E/Y/4mm/V5.0	6.1.2		NVSS_V26.1.0.2021
Network Customization		2	IPC/PTZ	Logout	192.168.1.2	1		TC-C32TS SPEC:18/	A/E/Y/M/H/2.7-13.5mm/V4.1	6.1.2	485407C308	NVSS_V30.0.0.2022
Codec Settings				-								_
OSD Settings												
NTP Settings												
Remote Service												
Access Platform												
Add Device												
Clear Added Device												
Search Setting												
Activate Device												
Disk Cleanup												
Advance Search Config												
WireLessRouteSet												
	_	-	-				-			_		
	Device	e: 2 C	ount: 2									